IHC

U0002.S.T30.K5S.E1.E2.M2.M3.C1.YS.W1S.W2.W9 – HOSPITAL BED 4 MOTORIZED

Images are only for orientative purpose, based on configuration the real product may differ slightly.

TECHNICAL SPECIFICATION

- Low bed for patient fall protection.
- The hospital bed is modern, electric, silent, made of high-quality, durable materials, suitable for hospital use.
- It complies with international and European safety standards and bear the CE marking.
- The lying surface: 86 cm × 191 cm, consisting of four sections (back, seat, thigh, leg), made of metal sections with removable plastic covers for easy cleaning. YS
- It is robust and suitable for patients up to 230 kg.
- The external dimensions are 102 cm width and 215 cm lenght, excluding extension.
- It includes an integrated length extension of 27 cm, usable without tools for taller patients. W9
- The head and foot boards are easily removable, made of durable plastic, and easy to clean and disinfect.
- The bed have side safety rails, divided into two parts on each side (four total). Each one have an easy-fold mechanism, operate independently, and include an ergonomic handle. The rails cover the entire lying length, be 40 cm height, and have tilt indicators for patient safety. K5S.
- Electric adjustment via a wired hand controller for height, backrest, and thigh/hip sections. C1.
- The same hand controller allows nursing staff to adjust CPR and Trendelenburg positions and include position-lock settings.

IHC

- There is also a central nurse control panel mounted on the footboard, wired, including all previous functions. E2.
- 11. Specifications:
- a. Height range: 36 - 78 cm.
- b. Back section: 70°, with automatic sliding mechanism to prevent patient slipping.
- c. Thigh section: 31°.
- d. Trendelenburg tilt: 12–15° electric.
- e. CPR emergency system: back rest motor with manual cpr and electronic cpr. M2, C1
- The bed have two IV pole sockets (left and right upper ends) and one traction pole socket in the center, as well as at the foot end.
- Each bed is delivered with one stainless-steel IV pole (at least two hooks), one traction pole, and two hooks on the chassis for urine bag holders (both sides). W1S , W2.
- Equipped with four 150 mm diameter castors, 360° swiveling, with a central foot brake. T30.
- The floor clearance (floor to chassis) is 15 cm for hoist access and cleaning. 15.
- The bed has bumpers on all four corners for protection during movement.
- The design allows effective cleaning, with smooth, rounded surfaces.
- The bed equipped with a battery backup for at least 2 hours of continuous operation in case of a power failure. E1.

CE